

Perforation Services

- Consulting
- Product Development
- Pilot Run / Pilot Production
- Contract Perforation




Perforation services

- Consulting
- Product Development
- Pilot Run / Pilot Production
- Contract Perforation

Machine	Roll to roll perforation machine: — Unwinding — Hot or cold-perforation — Slitting — Rewinding
Perforating width	Up to 1'580 mm
Reel diameter	Maximum 800 mm
Core diameter	Standard 3" or 6" (76 mm or 152 mm) Other dimensions on request
Reel weight	Web Width Max. Roll weight 1'600 – 1'200 mm 500 kg 1'000 mm 400 kg 800 mm 300 kg
Perforation-rings	Range of density up to 150 needles/cm² Needle diameter 0.05–3.0 mm
Micro perforation	Hole Ø 0.02 mm to 0.1 mm
Macro perforation	Maximum hole ∅ 3.0 mm
Counter roller	Brush, rubber, felt, special rollers
Heating	Internal- or external heating
Heating temperatures	Up to 300 °C (measured on perforation rings)
Line speed	Maximum 150 m/min
Perforation materials	Plastic: BOPP, oPP, PET, PS, PVC, PE, others. Aluminium Leather, artificial leather Nonwoven, nonwoven-laminate (20–90 gsm)







Please contact us for more detailed information