

## **Perforation Services**

- Consulting
- Product Development
- Pilot Run / Zero Series
- Contract Perforation




## **Perforation services**

- Consulting
- Product Development
- Pilot Run / Zero Series
- Contract Perforation

Maschine	Roll to roll perforation machine: – Winding up – Hot or cold-perforation – Slitting – Unwinding
Perforating width	Up to 1'600 mm
Reel diameter	Maximum 800 mm
Core diameter	Standard 3" (76 mm), other dimensions on request
Reel weight	Maximum 800 kg
Perforation-rings	Range of density up to 150 needles/cm <sup>2</sup> Needle diameter 0.05–3.0 mm
Micro perforation	Hole $\varnothing$ 0.02 mm to 0.1 mm
Macro perforation	Maximum hole $\varnothing$ 3.0 mm
Counter roller	Brush, rubber, felt
Heating	Internal- or external heating
Heating temperatures	Up to 300 °C (measured on perforation rings)
Line speed	Maximum 150 m/min
Perforation materials	Plastic: oPP, PET, PS, PVC, PE, others. Aluminium Leather, artificial leather Nonwoven, nonwoven-laminate (20–90 gsm)









Pfarrgasse 11, CH-4019 Basel Switzerland Tel +41 61 638 18 00 Fax +41 61 638 18 50 info@burckhardt.com

www.burckhardt.com

Please contact us for more detailed information