



High-end Perforating Unit PREMIUM

| Machine Type | Hot or Cold Pin Perforating Unit |
|------------------------|--|
| Machine name | Premium |
| Description | Strong frame Cassette design for high pressure or high precision perforation |
| Working width | Up to 4000 mm |
| Perforating roller | Roller Ø 180–350 mm Perforating segments according to customer's specification Ø over pin tips: 230–400 mm |
| Counter Roller | Roller Ø 200–400 mm Tampico fibre brush Options: (according to application) ■ Rubber ■ Felt ■ Female Roller |
| Heating system | Internal thermo-fluid heating up to 250 °C (measured at perforating ring) Options: Induction heating Internal electric resistance heating no heating |
| Drive system | 1 or 2 servo motors, up to 7.5 kW Option: synchronization of the two motors for male/female perforation |
| Line Speed | Up to 250 m/min (technical speed up to 400 m/min) |
| Emergency break system | Motor-brake |
| Penetration adjustment | Electric spindle-lifting device |
| Electronic control | SPS Control panel with touch screen, digital display suitable for integration into existing line |
| External dimensions | Total length = working width + 750 mm (motor) + 400 in case of internal oil heating Height: approx. 1300 mm Depth: approx. 860 mm |
| Additional options | Unit can be installed in horizontal position Electronic matching control for printed film perforation |





5 Touch-screen panel

For all machine types we are able to adapt to customer's requirements to ensure an optimal end-result.



CHRISTOPH BURCKHARDT AG

Pfarrgasse 11, CH-4019 Basel Switzerland Tel +41 61 638 18 00 Fax +41 61 638 18 50 info@burckhardt.com

www.burckhardt.com

Please contact us for more detailed information